

Craftsman 140cc* High Wheel Side Discharge Push Mower 50 States

Sears Item# 07137010000 | Model# 37010

\$199.98 Great Price

Sold by Sears

Product Description

No prime, no choke. Smooth Start™ Plus engines feature three advanced engine features.

- Powered by a Briggs & Stratton® Gold Engine Series 140cc* OHV engine (5.5 ft-lbs gross torque) for dependable starting performance, durability and long life
- Smooth Start[™] Plus engines feature three advanced engine features. The recoil starter allows for lower speed and effort during pulling. Ready Start[™] — No prime, no choke, just pull starter rope. Starting your mower has never been easier. Most Reliable Starting (MRS) spark plug – makes starting easier and lasts longer.
- 21 in. 2-in-1 domed deck Side discharge or mulch to put nutrients back into the lawn
- Deck design extends beyond wheels for more precise trimming and edging
- Save time with dual-point deck height adjusters with 6 positions
- Flexible cutting heights ranging from 1.25 to 3.75 in. for any lawn or grass type
- 3-position handle is adjustable to user height for maximum comfort
- 7 in. front and 11 in. rear wheels make it easy to maneuver over all types of terrain
- Mulch plug built into the deck Recycle the clippings and encourage a healthier lawn

- · Side discharge chute included
- Unit comes fully assembled No tools required
- 2-year full warranty
- Available in 50 states

Wheels & Tires:

Specifications & Dimensions Color and Styling: Color/Finish: Red **Product Overview:** 2 Year General Warranty: Mulch Ready: Yes Included with Item: Engine Oil Included: Yes Item Weight (lbs.): 61 Handles: Adjustable Handle: Yes Handle Material: Steel Handles Fold For Easy Storage: Yes Number of Handle Height Positions: 2-position Installation Requirements: Assembly Required: Fully Assembled Blade: Number of Cutting Positions: 6 Motor-Engine: Engine Brand: Briggs & Stratton(r) Engine Cycles: 4-cycle Engine Series: 550ex Gold Engine Series OHV Engine Size (cc): 140 Maximum Torque (ft-lb): 5.5 Oil Filter: No

^{*}As rated by the engine manufacturer Added on November 04, 2011

Front Tire Size:	7 in.
Rear Tire Size:	11 in.
Cut:	
Cutting Height Adjustment Type:	Dual
Cutting Height Range:	1-1/4 to 3-3/4 in.
Cutting Width (In.):	21
Disposal:	
Disposal by Side Discharge:	Yes - included
Bags:	
Bag Material:	Cloth
Certifications	
Location:	50 State