

RESISTANCE VALUES IN OHMS @ 70° F

Effective 12-01-02, Highlighted models indicate new generator head design. Verify model number when looking for values.
Highlight Models do not require you to order the Focus Mount Kit. It is welded to the frame.

MODEL NUMBERS	MAIN WINDINGS	AUXILARY WINDING	ROTOR	IDLE CONTROL	DC OUTPUT
	RED to GREEN BLACK to ORANGE	PINK CAPACITOR LEADS			
BS500	.430 - .470	2.15 - 2.29	1.81 - 1.92	N/A	N/A
BS525-W	.430 - .470	2.15 - 2.29	1.81 - 1.92	N/A	N/A
BS600	.320 - .350	1.50 - 1.60	1.44 - 1.52	N/A	N/A
BS600-W	.320 - .350	1.50 - 1.60	1.44 - 1.52	N/A	N/A
BS600-W-1	.320 - .350	1.50 - 1.60	1.44 - 1.52	N/A	N/A
BSI525-W	.420 - .450	2.24 - 2.34	1.81 - 1.92	N/A	N/A
BSI525-W-1	.40 - .50	2.55 - 2.75	1.64 - 1.82	N/A	N/A
BSI525-W-2	.40 - .50	2.55 - 2.75	1.64 - 1.82	N/A	N/A
BSI550-W	.260 - .280	1.60 - 1.71	1.80 - 1.87	N/A	N/A
BSI550-W-1	.260 - .280	1.60 - 1.71	1.80 - 1.87	N/A	N/A
BSI550-W-2	.250 - .280	1.48 - 1.62	1.62 - 1.74	N/A	N/A
BSI550-W-3	.250 - .280	1.48 - 1.62	1.62 - 1.74	N/A	N/A
BSV550-W	.250 - .280	1.48 - 1.62	1.62 - 1.74	N/A	N/A
BSV750-W	.130 - .145	.950 - 1.20	1.43 - 1.53	.170 - .210	.082 - .097
BSV750-W-1	.130 - .145	.950 - 1.20	1.43 - 1.53	.170 - .210	.082 - .097
BSV750-W-2	.130 - .145	.950 - 1.20	1.43 - 1.53	.170 - .210	.082 - .097
BSV750-W-3	.130 - .145	.900 - 1.20	1.31 - 1.46	.150 - .210	.073 - .097
BSV800	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
BSV800-1	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
CDGT3010	.260 - .280	2.15 - 2.29	1.82 - 1.93	N/A	N/A
CDGT3010-1	.260 - .280	2.15 - 2.29	1.82 - 1.93	N/A	N/A
CDGT3010-2	.210 - .240	2.55 - 2.72	1.80 - 1.90	N/A	N/A
CDGT3010-3	.210 - .240	2.55 - 2.72	1.64 - 1.78	N/A	N/A
CGBV4000	.430 - .470	1.78 - 1.82	1.80 - 1.87	.180 - .230	.080 - .120
CGBV4000-1	.430 - .470	1.78 - 1.82	1.80 - 1.87	.180 - .230	.080 - .120
CGTP3000	.260 - .280	2.15 - 2.29	1.82 - 1.93	N/A	N/A
CGTP3000-1	.260 - .280	2.15 - 2.29	1.82 - 1.93	N/A	N/A
CGTP3000-2	.210 - .240	2.55 - 2.72	1.80 - 1.90	N/A	N/A
CGTP3000-3	.210 - .240	2.55 - 2.72	1.64 - 1.78	N/A	N/A
CH250	.210 - .240	2.55 - 2.72	1.80 - 1.87	N/A	N/A
CH250-1	.210 - .240	2.55 - 2.73	1.64 - 1.78	N/A	N/A
CH350CS	.430 - .470	2.66 - 2.83	1.80 - 1.87	.250 - .280	.110 - .140
CH350CS-1	.430 - .470	2.66 - 2.83	1.80 - 1.87	.250 - .280	.110 - .140
CH350CS-2	.420 - .480	2.63 - 2.86	1.64 - 1.82	.240 - .290	.100 - .150
CH350IS	.420 - .480	2.63 - 2.86	1.64 - 1.82	.240 - .290	.100 - .150
CH350IS-1	.420 - .480	2.63 - 2.86	1.64 - 1.82	.240 - .290	.100 - .150
CTE300	.260 - .280	2.15 - 2.29	1.82 - 1.90	N/A	N/A
CTE300-1	.210 - .240	2.55 - 2.72	1.64 - 1.78	N/A	N/A
DBSI325	.210 - .240	2.55 - 2.72	1.80 - 1.87	N/A	N/A
DBSI325-1	.210 - .240	2.55 - 2.72	1.64 - 1.78	N/A	N/A
DGHC6510-WK	.180 - .150	.935 - 1.00	1.52 - 1.43	.150 - .170	.055 - .085
DGT5010-WK-1	.430 - .470	2.15 - 2.29	1.81 - 1.92	N/A	N/A
DTE325	.210 - .240	2.55 - 2.72	1.80 - 1.87	N/A	N/A
DTE325-1	.210 - .240	2.55 - 2.72	1.80 - 1.87	N/A	N/A
DTE325-2	.210 - .240	2.55 - 2.72	1.64 - 1.78	N/A	N/A
EXGB4010-2	.520 - .560	2.15 - 2.29	1.81 - 1.92	N/A	N/A
EXGB5010-1	.452 - .470	1.36 - 1.40	1.15 - 1.18	N/A	N/A
EXGB5010-2	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
EXGBV7010-3	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
EXGHV4510	.425 - .470	1.36 - 1.40	1.15 - 1.18	N/A	N/A
EXGHV4510-1	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
EXGHV4510-2	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GB4000	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GB4000-1	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GB4000-2	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GB4000-3	.520 - .560	2.15 - 2.29	1.81 - 1.92	N/A	N/A
GB4010	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GB4010-1	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GB4010-2	.520 - .560	2.15 - 2.29	1.81 - 1.92	N/A	N/A
GB5000	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GB5000-1	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GB5000-2	.470 - .510	1.57 - 1.68	1.15 - 1.18	N/A	N/A
GB5000-3	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GB5000-4	.430 - .470	2.15 - 2.29	1.81 - 1.92	N/A	N/A

GB5000-WK-2	.470 - .452	1.40 - 1.36	1.15 - 1.18	N/A	N/A
GB5000-WK-3	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GB5010	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GB5010-1	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GB5010-2	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GBE4010	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GBE4010-1	.520 - .560	2.15 - 2.29	1.81 - 1.92	N/A	N/A
GBFE6010	.320 - .350	1.50 - 1.60	1.44 - 1.52	N/A	N/A
GBFE6010-1	.320 - .350	1.50 - 1.60	1.44 - 1.52	N/A	N/A
GBO5250-WK	.420 - .450	2.66 - 2.78	1.80 - 1.90	N/A	N/A
GBO5250-WK-2	.40 - .50	2.55 - 2.75	1.64 - 1.82	N/A	N/A
GBP4000	.464 - .483	1.51 - 1.58	1.81 - 1.92	N/A	N/A
GBP4000-1	.520 - .560	2.15 - 2.29	1.81 - 1.92	N/A	N/A
GBV4600	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GBV5000	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GBV5000-1	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GBV7000	.168 - .177	.798 - .816	.5 - .9	N/A	N/A
GBV7000-1	.168 - .177	.798 - .816	.5 - .9	N/A	N/A
GBV7000-2	.168 - .177	.798 - .816	.5 - .9	N/A	N/A
GBV7000-3	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
GBV7000-4	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
GBV7010	.168 - .177	.798 - .816	.5 - .9	N/A	N/A
GBV7010-1	.168 - .177	.798 - .816	.5 - .9	N/A	N/A
GBV7010-2	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
GBV7010-3	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
GBVE7500-WK	.130 - .145	.950 - 1.20	1.43 - 1.53	.170 - .210	.082 - .097
GBVE8000-WK	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
GBVE8000-WK-1	.160 - .180	1.45 - 1.55	1.43 - 1.52	N/A	N/A
GBVF5000	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GBVF5000-1	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
GH4501	.370 - .400	2.53 - 2.70	1.80 - 1.87	.220 - .250	.110 - .130
GH4501-1	.360 - .390	2.25 - 2.42	1.62 - 1.74	.230 - .270	.100 - .120
GHE10000-WK-1	.08 - .12	.42 - .46	1.44 - 1.58	.15 - .19	.07 - .11
GHV4250C	.460 - .480	1.64 - 1.73	1.80 - 1.87	N/A	N/A
GHV4500	.470 - .452	1.36 - 1.40	1.15 - 1.18	N/A	N/A
GHV4500-1	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GHV4500-2	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GHV4500-3	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GM1000					
GT5000	.430 - .470	2.15 - 2.29	1.81 - 1.92	N/A	N/A
GT5000C	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GT5000C-1	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
GT5250-1	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GT5250-2	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
GT5250-WK	.470 - .510	1.57 - 1.68	1.80 - 1.87	N/A	N/A
GT5250-WK-1	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
GT5250-WK-2	.360 - .390	2.25 - 2.42	1.62 - 1.74	N/A	N/A
GT5251	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
GT5251-1	.360 - .390	2.25 - 2.42	1.62 - 1.74	N/A	N/A
GTO5200C-WK	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
GTO5200C-WK-1	.360 - .390	2.25 - 2.42	1.62 - 1.74	N/A	N/A
H1000	0.075	1.3	5.23	.15 - .19	.07 - .11
H1000-1	.08 - .12	.42 - .46	1.44 - 1.58	.15 - .19	.07 - .11
H1000IS-W	.08 - .12	.42 - .46	1.44 - 1.58	.15 - .19	.07 - .11
H1000IS-W-1	.08 - .12	.42 - .46	1.44 - 1.58	.15 - .19	.07 - .11
H450CS	.370 - .400	2.53 - 2.70	1.80 - 1.87	.220 - .250	.110 - .130
H450CS-1	.370 - .400	2.53 - 2.70	1.80 - 1.87	.220 - .250	.110 - .130
H450CS-2	.360 - .390	2.25 - 2.42	1.62 - 1.74	.230 - .270	.100 - .120
H450IS-W	.360 - .390	2.25 - 2.42	1.62 - 1.74	.230 - .270	.100 - .120
H451CS-W	.220 - .250	1.88 - 2.01	1.33 - 1.42	.150 - .176	.07 - .08
H451CS-W-1	.220 - .250	1.88 - 2.01	1.33 - 1.42	.150 - .176	.07 - .08
H451CS-W-2	.220 - .250	1.88 - 2.01	1.33 - 1.42	.150 - .176	.07 - .08
H451CS-W-3	.221 - .237	1.83 - 1.97	1.68 - 1.76	.149 - .163	.055 - .077
H650CS	.180 - .150	.935 - 1.00	1.52 - 1.43	.150 - .170	.055 - .085
H650CS-1	.180 - .150	.935 - 1.00	1.52 - 1.43	.150 - .170	.055 - .085
H650CS-2	.130 - .145	.900 - 1.20	1.31 - 1.46	.150 - .210	.073 - .097
H650IS-W	.180 - .150	.935 - 1.00	1.52 - 1.43	.150 - .170	.055 - .085
H650IS-W-1	.130 - .145	.900 - 1.20	1.31 - 1.46	.150 - .210	.073 - .097
PGN350	.210 - .250	2.67 - 2.85	1.64 - 1.82	N/A	N/A
PH350IS	.210 - .250	2.67 - 2.85	1.64 - 1.82	N/A	N/A

T525	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A
T550-W	.370 - .400	2.50 - 2.65	1.80 - 1.87	N/A	N/A